



## PRO-PACK MATERIALS PTE. LTD.

Blk 970, Toa Payoh North, # 04-18, Toa Payoh Industrial Estate,  
Singapore 318992.

Tel: (65) 63541511 Fax: (65) 63541711

Website : [www.pro-pack.com.sg](http://www.pro-pack.com.sg)

### **SPECIFICATION FOR HAKKO SMOKE ABSORBER** **MODEL NO: HAKKO FA430**



Parameters	Details
Power consumption	120 W
Noise level	50 dB
Maximum suction capacity	With single duct: MAX. 4.1m <sup>3</sup> /min. (145 CFM) With two ducts : MAX. 4.7m <sup>3</sup> /min. (167 CFM)
Filtering efficiency	99.97% 0.3 μm (LOW, MEDIUM mode) 99.96% 0.3 μm (HIGH mode)
Static pressure	1,500 Pa
Duct set (sold separately)	Length of duct : Φ55 mm × 1.2 m (ESD SAFE)
Dimensions	330(W) × 366(H) × 343(D) mm
Weight	7.5 kg

- Weight (w/o cord)
- Filtering efficiency is an initial value of collection efficiency based on counting method for air borne dust collected by a single plate of filter (unfolded).
- Noise level is measured at a distance of 1 m from the face of unit in a anechoic room
- Net in duct sets are not protected against electrostatic discharge

\*\*\*\*\*