



PRO-PACK MATERIALS PTE. LTD.

Blk 970, Toa Payoh North, #04-18, Toa Payoh Industrial Estate,
Singapore 318992.

Tel: (65) 63541511 Fax: (65) 63541711

Website : www.pro-pack.com.sg

SPECIFICATION FOR VACUUM DESICCATOR

MODEL NO: PPMVDC-41



- Fitted with airtight silicon gasket to maintain vacuum condition without any grease.
- Highly transparent Polycarbonate which allows for clear sample viewing, non-corrosive and it is easy to clean and maintain.
- Allow various experiments under non vacuum conditions.
- Lock holds the bottoms and top lid together under non vacuum conditions.

Model:		PPMVDC-41
Internal volume(L)		45L
Gauge range (Mpa)		0 to -0.1 (Analog)
Nozzle (mm)		9.5
Max. Permissible Vacuum		1.33×10^{-4} Mpa (Analog)
Max. Load (Kg)/for Shelf		5Kg
No. of Shelves (included/max.)		3/6
Material	Bodies	PC (Polycarbonate)
	Perforate tray	PC (Polycarbonate)
	Tray/Locker	PC (Polycarbonate)
	Vacuum Seal	Silicone Rubber
Dimension (WxDxH)	Internal(mm)	355x374x445
	Exterior(mm)	420x397x491
Net Weight (Kg)		12.2Kg
Cat. No.	Without UV Block Effect	AAAD4031
	With UV Block Effect	AAAD411